

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) Franking machine with at least one print head of an inkjet print mechanism for printing flat postal objects such as letters or postcards insertable into or passing through the machine, comprised of a guide part arranged so as to project about the print head and further relative to a ~~its~~ jet opening plane of the print head, having correlated therewith a transport device for transporting the postal objects between the print head ~~it~~ and oppositely positioned conveying rollers rotating about axes oriented transverse to the conveying direction, wherein the transport device has two drive rollers connected in driving connection with one another and forming together with the guide part a conveying path, which drive rollers, when viewed in the conveying direction, are arranged before and behind the print head, and has a counterpressure roller arranged opposite thereto, respectively, which exerts a pressure against one

drive roller or the postal object transported therebetween and which is reversibly liftable, and comprising a device for maintaining, cleaning and servicing the print head, wherein, when the counterpressure rollers (13, 15) are lowered, a service slide (221), arranged on a guide arrangement (225) so as to be drivingly movable transverse to the conveying direction of the postal objects, is moveable into a service position which is arranged underneath the print head (228).

2. (Previously presented) Machine according to claim 1, wherein the guide part (229) is adjustable by means of a control lever (244) connected with the main shaft into a position which is retracted relative to the jet opening plane of the print head (228).
3. (Currently amended) Machine according to claim 1, wherein the service slide (201) has a ~~at its~~ rear end ~~is~~ connected with an eccentric pin (221) fastened to a control disk (218) drivable about a vertical axis.
4. (Previously presented) Machine according to claim 1, wherein the service slide (201) at the forward end has a wiper lip

(209) extending transversely to the direction of movement and acting during movement of the service slide (201) onto the projecting jet opening plane of the print head (228).

5. (Previously presented) Machine according to claim 4, wherein the wiper lip (209) is supported against a spring force on the guide part (229) and passes across the jet opening plane during the sliding movements of the service slide (201).
6. (Previously presented) Machine according to claim 4, wherein the wiper lip (209) is arranged in a catch basin (211).
7. (Previously presented) Machine according to claim 4, wherein the service slide (201) in the advancing direction has at least one sealing bell (203) which is arranged behind the wiper lip (209) and covers the nozzle opening plane of a print head (228) and can be pressed against the plane by being lifted.
8. (Previously presented) Machine according to claim 7, wherein the service slide (201) comprises a Scotch-yoke groove (215) as a connecting device to the control disk (218) for

receiving the eccentric pin (221), wherein the groove secures the service slide (201) in the service position when the eccentric pin (221) passes through and, upon further rotational movement of the control disk (218) connected in driving connection with the guide arrangement (225), the service slide (201) is locked in the service position by means of the lifting control curves (226A, 226B) provided on the guide arrangement (225), whereby the sealing bell (203) is pressed against the jet opening plane.

9. (Previously presented) Machine according to claim 8, wherein on the guide arrangement (225) a control pin (223) is fastened which engages the control curve provided on the control disk (218).
10. (Previously presented) Machine according to claim 7, wherein the controllable motor which is in drive connection with the control disk (218) having a freewheeling device is reversibly configured and in drive connection with a pump which is in communication with the sealing bell (203).
11. (Previously presented) Machine according to claim 10, wherein

FE-16

the pump is connected by a suction line with the catch basin (211) correlated with the wiper lip (209).

12. (Previously presented) Machine according to claim 7, wherein the pump is connected to the ink source by a suction line via the sealing bell (203) connected in the service position to the print head/the print heads (228).
13. (Previously presented) Machine according to claim 12, wherein the print head/the print heads (228) and the ink source are connected by a portion of the suction line.
14. (Previously presented) Machine according to claim 3, wherein the control disk (218) comprises a switching cam cooperating with a switch (224) and correlated with the initial position of the service slide (201).